



Shell Helix *Extra HX8 5W-40*

Fully synthetic motor oil - Enhance your engine's efficiency by reducing friction for optimized performance.

Shell Helix Extra HX8 fully synthetic motor oil works hard to help keeping modern engines running efficiently and well protected. With Anti-Friction Technology, it helps to reduce engine frictions to provide enhanced fuel economy and protection suitable for all OEM-recommended drain intervals.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- **Superior active cleansing technology**¹
Actively locks away harmful performance-robbing deposits.
- **Active clean-up**
Helps to remove sludge left behind by inferior oils²
- **Excellent wear protection**³
Helps to extend engine life by protecting against wear, even in the toughest driving conditions.
- **Long-term resistance to oil degradation**
Helps to maintain protection throughout the oil-drain interval.
- **Long life**
Suitable for all equipment-manufacturer-recommended oil-drain intervals.
- **Enhanced low-temperature performance**
Faster oil flow for quicker engine warm-up⁴
- **Low-evaporation formulation**⁵
Low oil consumption for less frequent top-up.
- **Multi-fuel capability**
Can be used for gasoline, diesel and gas engines, and is also suitable for biodiesel and gasoline/ethanol blends.
- **Low Speed Pre-Ignition Protection (LSPI)**
The latest highly rated turbocharged gasoline direct injection engines can be vulnerable to damaging LSPI events resulting from uncontrolled ignition of the fuel.

¹ Compared with Shell Helix mineral oils

² Based on a severe sludge clean-up test

³ Based on Sequence IVA engine test carried out at an independent laboratory

⁴ Compared with higher-viscosity oils

⁵ Based on NOACK volatility test and equipment manufacturers' requirements

Main Applications

- Shell Helix Extra HX8's fully synthetic formulation can be used in engines in a wide variety of modern vehicles that face these demanding driving conditions, and can be recommended for customers who want to keep the same oil-drain interval, operating in extreme climates or driving in congested stop-start city traffic.
- Shell Helix Extra HX8 can be used for gasoline engines, diesel engines (without particulate filters) and gas engines, and it is also suitable for use with biodiesel and gasoline/ethanol blends.
- It is also suitable for use in modern direct injection turbocharged gasoline engines where it provides protection against damaging low-speed pre-ignition (LSPI).

Specifications, Approvals & Recommendations

- API SP
- ACEA A3/B4
- Meets requirements MB 229.3
- Meets the requirements of Fiat (FCA) 9.55535-M2, Renault RN 0700/0710

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at:
<https://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix Extra HX8 5W-40
Density	@15°C	kg/m ³	ASTM D4052	841
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.8
Kinematic Viscosity	@40°C	cSt	ASTM D445	89.2
Flash Point		°C	ASTM D92	232
Pour Point		°C	ASTM D97	-36

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on health and safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from <https://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.